

Tabla No 5 Valores de F de Christiansen

Valores del factor de reducción de Christiansen ($S_0 = S$)						
N	m = 1.75	m = 1.80	m = 1.85	m = 1.90	m = 2.00	
1	1	1	1	1	1	1
2	0.65	0.644	0.639	0.634	0.625	
3	0.546	0.54	0.535	0.528	0.518	
4	0.497	0.491	0.486	0.48	0.469	
5	0.469	0.463	0.457	0.451	0.44	
6	0.451	0.445	0.435	0.433	0.421	
7	0.438	0.432	0.4125	0.419	0.408	
8	0.428	0.422	0.415	0.041	0.398	
9	0.421	0.414	0.409	0.402	0.391	
10	0.415	0.409	0.402	0.396	0.385	
11	0.41	0.404	0.397	0.392	0.38	
12	0.406	0.4	0.394	0.388	0.376	
13	0.403	0.396	0.391	0.384	0.373	
14	0.4	0.394	0.387	0.381	0.37	
15	0.397	0.391	0.384	0.379	0.367	
16	0.395	0.389	0.382	0.377	0.365	
17	0.393	0.387	0.38	0.375	0.363	
18	0.392	0.385	0.379	0.373	0.361	
19	0.39	0.384	0.377	0.372	0.36	
20	0.389	0.382	0.376	0.37	0.359	
22	0.387	0.38	0.374	0.368	0.357	
24	0.385	0.378	0.372	0.366	0.355	
26	0.383	0.376	0.37	0.364	0.353	
28	0.382	0.375	0.369	0.363	0.351	
30	0.38	0.374	0.368	0.362	0.35	
35	0.378	0.371	0.365	0.359	0.347	
40	0.376	0.37	0.364	0.357	0.345	
50	0.374	0.367	0.361	0.355	0.343	
100	0.369	0.362	0.356	0.35	0.338	
□	0.364	0.357	0.351	0.345	0.333	

m: indicador del régimen hidráulico (1.75 para PE; 1.80 para PVC y 1.9 para aluminio).
 N: Número de salidas.